

# DC101R4.7

DC101,W/2,4.7K,RES,IN,SER & PAR,SFT,SPVD

## DC101-Series

---

The DC101-Series surface mount magnetic contacts are designed for use in installations where a small, sealed unit is required. The reed switch is totally encapsulated in an exclusive polyurethane potting compound preventing moisture from entering the switch and causing false alarms.

## Easy installation

---

The 16 mm standard gap distance allows for fast, easy installation and prevents false alarms from loose fitting doors. Recessed mounting holes make for clean-looking installations.

## High Quality components and materials

---

Reed legs are plated with rhodium or ruthenium, and hermetically sealed in dry nitrogen. This offers superior protection against sticking and provides a moisture free environment therefore preventing corrosion.



## Standard Features

---

- Convenient surface mounting
- Standard 2 m wire length
- Tamper loop provided
- Neat and tidy design

# DC101R4.7

DC101,W/2,4.7K,RES,IN,SER & PAR,SFT,SPVD

## Specifications

General	
Application type	Surface Mount
Contact type	4K7 resistor
Connectivity	4 wires, 2.5 m
Wired/wireless	
Wired-wireless	Wired
Physical	
Operating gap	15 mm
Standards & regulation	
EN50131 grade	Grade 2

## Ordering Information

Part No.	Description
DC101R4.7	DC101,W/2,4.7K,RES,IN,SER & PAR,SFT,SPVD

